

Gprinter 3" Direct Thermal Barcode Label Printers

GP-3150TIN

Features:

- 6 inch/s high-speed printing
- 80mm paper exit chute
- Support media width from 24mm to 82mm
- Multiple interfaces for different connectivity
- Supports two-dimensional barcode printing
- Support label peel-off and tear-off modes
- Compatible with various label softwares
- Support 2M DRAM & FLASH memory
- Support BMP/PCX/BAS files download and memory
- 100MB Ethernet for faster connection to avoid label losing
- Support English, Chinese and Korean languages etc.
- Modular designs will satisfy different Customers' printing demand
- Support Thermal paper, Thermal label, Adhesive thermal paper etc.
- Automatic paper adjusting and auto temperature control for durable printing
- Easy paper feeding and user-friendly control

GP-3120TN & GP-3120TL & GP-3120TU

Features:

- Build-in power adapter (for GP-3120TL)
- 5 inch/s high-speed printing
- 80mm paper exit chute
- Label tear off mode
- Compatible with various label softwares
- Support 2M DRAM & FLASH memory
- Support BMP/PCX/BAS files download
- Support English, Chinese and Korean languages etc.
- Modular designs will satisfy different Customers' printing demand
- Support Thermal paper, Thermal label, Adhesive thermal paper etc.
- Automatic paper adjusting
- Auto temperature control for durable printing
- Easy paper feeding and user-friendly control



SPECIFICATIONS	GP-3150TIN	GP-3120TN	GP-3120TL	GP-3120TU
PRINTING	Print Method			
	Direct thermal line			
	Resolution			
	203 dpi			
	Print Width			
	Max 76mm			
	Print Speed	3 ~ 6inch/s	3 ~ 5inch/s	2 ~ 5inch/s
	Interface	USB+Serial+Ethernet	USB+Serial	USB
	Print head temperature detect	Thermal sensitive resistance		
	Print Head Position detect	Microswitch		
MEDIA	Paper sensor	Photoelectric sensor		
	Memory	DRAM: 2M FLASH: 2M		
	Command set	TSPL		
	Paper Type	Thermal paper, Thermal label, Adhesive thermal paper		
	Media Width	24-82mm	20-82mm	20-80mm
CHARACTER FONT BARCODE TYPE GRAPHICS SOFTWARE	Media Diameter	25 ~ 85mm	25 ~ 85mm	25 ~ 100mm
	Paper Off Type	Tear off or peel-off	Tear off	Tear off
	Enlargement&Rotation	1 ~ 10 times enlargement in both directions; 0°、90°、270°、360°rotation		
	Character Size	Font 0 ~ Font 8		
OPERATIONAL CHARACTERITIES	2D Barcode	QR code		
	Graphics Processing	Support BMP/PCX/BAS files		
	Editing Software	Nicelabel SE		
	Driver	Windows 2000、XP、Vista、Win7、Win8、Windows Server 2003&2008 etc.		
PHYSICAL PROPERTIES	DLL	Windows 2000、XP and Vista		
	Cashdrawer Out	24VDC/2A		
	Power Supply	AC 110V/220V, 50 ~ 60Hz, DC 24V/2A		
	Work Environment	Temperature: 5 ~ 45℃, Humidity: 20 ~ 80%		
	Storage Environment	Temperature: -40 ~ 55℃, Humidity: 10 ~ 93%		
	Weight	1.65kg	1.5kg	1.4kg
	Dimension	156×230×147mm	150×220×150mm	215×148×155mm
				1.5kg
				227×152×143mm